

2-WIRE ROUND/RECTANGULAR ZONE DAMPERS

The D Series dampers are galvanized steel, single-blade dampers with a 24 volt spring return actuator. These dampers are shipped complete and ready for installation. They are rated for duct systems with less than 1.0" WC. The D Series damper has a simple adjustment for setting the minimum position.

Features and Benefits:

- Compatible with most zone control panels
- 24-gauge steel shell
- Tight seal gasket
- 24V synchronous motor
- Can be configured as PC/SO or PO/SC
- Quiet operation
- Simple adjustment for setting the minimum position

Warranty:

- 5 Years



Specifications:

Construction	24-gauge steel shell
Sizes	4", 5", 6", 7", 8", 9", 10", 12", 14", 16", 18", 20"
Damper Actuator Type	24VAC, 10VA, 2-wire power close/spring open

The HD Series dampers are extruded aluminum parallel blade dampers with a 24 volt spring return actuator. The HD Series dampers can be installed in any position. They are rated for duct systems with less than 1.0" WC. The damper has a simple adjustment for setting the minimum position.

Features and Benefits:

- Compatible with most zone control panels
- Extruded aluminum
- 24V synchronous motor
- Can be configured as PC/SO or PO/SC
- Quiet operation
- Simple adjustment for setting the minimum position

Warranty:

- 5 Years



Specifications:

Construction	Extruded aluminum
Sizes	6" x 6" to 36" x 24" side-mount or bottom-mount
Damper Actuator Type	24VAC, 10VA, 2-wire power close/spring open