

Nominal Size	Actual Size	Capacity (CFM)			Standard Capacity			Media Area	High Capacity			Media Area
		@300	@500	@625	@300 FPM	@500 FPM	@625 FPM		@300 FPM	@500 FPM	@625 FPM	
10x20x1	9.50 x 19.50 x .75	425	700	NR	0.26	0.51	NR	2.3	0.21	0.41	NR	2.9
12x24x1	11.38 x 23.38 x .75	600	1000	NR	0.26	0.51	NR	3.3	0.21	0.41	NR	4.2
14x20x1	13.50 x 19.50 x .75	590	980	NR	0.26	0.51	NR	3.3	0.21	0.41	NR	4.1
14x25x1	13.50 x 24.50 x .75	730	1215	NR	0.26	0.51	NR	4.1	0.21	0.41	NR	5.1
15x20x1	14.50 x 19.50 x .75	625	1050	NR	0.26	0.51	NR	3.5	0.21	0.41	NR	4.4
16x20x1	15.50 x 19.50 x .75	670	1115	NR	0.26	0.51	NR	3.8	0.21	0.41	NR	4.7
16x25x1	15.50 x 24.50 x .75	840	1400	NR	0.26	0.51	NR	4.7	0.21	0.41	NR	5.9
18x24x1	17.38 x 23.38 x .75	900	1500	NR	0.26	0.51	NR	5.1	0.21	0.41	NR	6.3
20x20x1	19.50 x 19.50 x .75	840	1400	NR	0.26	0.51	NR	4.8	0.21	0.41	NR	5.9
20x25x1	19.50 x 24.50 x .75	1050	1740	NR	0.26	0.51	NR	6	0.21	0.41	NR	7.4
24x24x1	23.38 x 23.38 x .75	1200	2000	NR	0.26	0.51	NR	6.8	0.21	0.41	NR	8.5
25x25x1	24.50 x 24.50 x .75	1310	2170	NR	0.26	0.51	NR	7.4	0.21	0.41	NR	9.3
10x20x2	9.50 x 19.50 x 1.75	425	700	875	0.14	0.25	0.34	4	0.09	0.18	0.25	6
12x20x2	11.50 x 19.50 x 1.75	500	840	1050	0.14	0.25	0.34	4.8	0.09	0.18	0.25	7.2
12x24x2	11.38 x 23.38 x 1.75	600	1000	1250	0.14	0.25	0.34	5.7	0.09	0.18	0.25	8.6
14x20x2	13.50 x 19.50 x 1.75	590	980	1215	0.14	0.25	0.34	5.6	0.09	0.18	0.25	8.4
14x25x2	13.50 x 24.50 x 1.75	730	1215	1520	0.14	0.25	0.34	7.1	0.09	0.18	0.25	10.6
15x20x2	14.50 x 19.50 x 1.75	625	1050	1310	0.14	0.25	0.34	6.1	0.09	0.18	0.25	9.1
16x20x2	15.50 x 19.50 x 1.75	670	1115	1400	0.14	0.25	0.34	6.7	0.09	0.18	0.25	9.9
16x24x2	15.50 x 23.50 x 1.75	800	1350	1675	0.14	0.25	0.34	7.8	0.09	0.18	0.25	11.6
16x25x2	15.50 x 24.50 x 1.75	840	1400	1740	0.14	0.25	0.34	8.1	0.09	0.18	0.25	12.1
18x24x2	17.50 x 23.50 x 1.75	900	1500	1875	0.14	0.25	0.34	8.8	0.09	0.18	0.25	13.1
20x20x2	19.50 x 19.50 x 1.75	840	1400	1740	0.14	0.25	0.34	8.3	0.09	0.18	0.25	12.4
20x24x2	19.50 x 23.50 x 1.75	1000	1675	2100	0.14	0.25	0.34	9.8	0.09	0.18	0.25	14.6
20x25x2	19.50 x 24.50 x 1.75	1050	1740	2170	0.14	0.25	0.34	10.5	0.09	0.18	0.25	15.5
24x24x2	23.38 x 23.38 x 1.75	1200	2000	2500	0.14	0.25	0.34	11.8	0.09	0.18	0.25	17.9
25x25x2	24.50 x 24.50 x 1.75	1310	2170	2720	0.14	0.25	0.34	12.8	0.09	0.18	0.25	19.1
12x24x4	11.38 x 23.38 x 3.75	600	1000	1250	0.09	0.18	0.25	10.6	0.08	0.16	0.23	12.9
16x20x4	15.50 x 19.50 x 3.75	670	1115	1400	0.09	0.18	0.25	12	0.08	0.16	0.23	14.7
16x24x4	15.38 x 23.38 x 3.75	800	1350	1675	0.09	0.18	0.25	14.3	0.08	0.16	0.23	17.5
16x25x4	15.50 x 24.50 x 3.75	840	1400	1750	0.09	0.18	0.25	15	0.08	0.16	0.23	18.4
18x24x4	17.50 x 23.38 x 3.75	900	1500	1875	0.09	0.18	0.25	16.3	0.08	0.16	0.23	19.9
20x20x4	19.50 x 19.50 x 3.75	840	1400	1740	0.09	0.18	0.25	15.1	0.08	0.16	0.23	18.4
20x24x4	19.50 x 23.38 x 3.75	1000	1675	2100	0.09	0.18	0.25	18.1	0.08	0.16	0.23	22.2
20x25x4	19.50 x 24.50 x 3.75	1050	1740	2170	0.09	0.18	0.25	19.5	0.08	0.16	0.23	23.6
24x24x4	23.38 x 23.38 x 3.75	1200	2000	2500	0.09	0.18	0.25	22.5	0.08	0.16	0.23	27.5
24x24x6	23.38 x 23.38 x 5.75	1200	2000	2500	0.13	0.19	0.29	33.3	0.11	0.17	0.28	40.7

Notes:

- MERV (Minimum Efficiency Reporting Value) • Recommended Final Pressure Drop is 1.0" w.g.
- Performance data is based on ASHRAE Test Standards 52.1-1999 and 52.2-2007. • Recommended maximum continuous operational temperature is 200° F.



KOCH FILTER®
PURE PERFORMANCE

8401 Air Commerce Drive, Louisville, KY 40219
toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
info@kochfilter.com | www.kochfilter.com