

VR8345

Universal Electronic Ignition Gas Valve

Honeywell



With universal application and an incredibly compact size that helps you work easily in tight spaces, the VR8345 is the only electronic ignition gas valve you need. The Honeywell VR8345

Universal Electronic Ignition Gas Valve helps you stay ready for any system — intermittent pilot, direct spark ignition, hot surface pilot — you come across, any day, every day, with just one gas valve. The high BTU/H capacity and multipoise mounting make the VR8345 even more versatile.

VR8345 Universal Electronic Ignition Gas Valve



Universal application. Compact size. High BTU/H capacity. Complete set of adapters. Simply put, you get it all with the VR8345.

UNIVERSAL APPLICATION

This one valve handles all of your intermittent pilot, direct spark ignition and hot surface pilot gas valve needs. The VR8345 even comes with a 1/2" reducer bushing and an LP conversion kit in case they're needed. You'll find everything you need for every job right in the box, so you can replace a wide range of Honeywell, White-Rodgers and Robertshaw models with just the VR8345.

- VR8345M: Standard Application
- VR8345Q: 2-Stage Application
- VR8345K: Slow Opening

Learn More

Call toll-free **1-800-328-5111**,
e-mail **info@honeywell.com**,
or visit **forwardthinking.honeywell.com**.

Automation and Control Solutions

In the U.S.:

Honeywell

1985 Douglas Drive North
Golden Valley, MN 55422-3992

In Canada:

Honeywell Limited

35 Dynamic Drive

Toronto, Ontario M1V 4Z9

www.honeywell.com

COMPACT SIZE

While you're saving space on your truck, you'll also save some skin on your knuckles. Because the amazing compactness of the VR8345 gives you room to work in all furnaces, space heaters, boilers, unit heaters and even pool heaters.

WIDE-CAPACITY CONTROL

The VR8345 has capacity covered for almost any IP, HSI or DSI gas-fired appliance. The minimum regulation is only 30,000 BTU/H for natural gas and 48,600 for LP gas, so you can use this valve for virtually all residential equipment. And the VR8345 works great for the big jobs, too, with a maximum regulation of 415,000 BTU/H for natural gas and 672,300 for LP gas.

MULTIPOISE MOUNTING

The swing radius for the VR8345 is a mere four inches, so it's easy to rotate the valve into position. And the multipoise mounting lets you install the VR8345 at any angle from 0° to 90° without affecting performance.

ADAPTER KIT

Every VR8345 valve comes supplied with two 1/2" reducer bushings, a terminal block jumper for IP/HSI/DSI selection, pilot plug and a natural gas to LP gas conversion kit. Quite simply, this valve is ready to tackle any job.

Follow us on Twitter:
@honeywellcpro



YouTube:
@honeywellcpro



Honeywell