ZONE CONTROL PANELS

These panels represent the most contractor-friendly zoning solution today. The ZP2 is a single-stage heat/cool panel designed to control 2 zones in residential and light commercial applications. The two ZP3 models are designed to fit three-zone applications for single-stage, multi-stage, heat pump or dual fuel systems in residential and light commercial applications. All panels can accommodate 2 or 3 wire zone dampers. Metal Enclosure (iO-PAN-ME) available as an additional option on iO Zone Panels.

Features and Benefits:

- Auto changeover
- · First call priority with time share
- Electronic discharge air sensor (sold separately)
- LED status indication
- · Independent fan control by zone
- Short cycle protection
- · Works with 2 or 3 wire zone dampers
- Purge cycle option (ZP3 panels only)

Warranty:

• 10 Years



ZP2-HC shown

Specifications:

Construction	Plastic enclosure with snap-on panel cover
Mounting	Snap track with 2 back plate screws
Dimensions	8.00" Height x 6.00" Width x 1.50" Depth
Operating Temperature	-40° F to 150° F
Time Delays	3 minutes off between cooling calls 3 minutes off on low limit 20 minute time share
Discharge Air Limits	Preset Low Limit (45° F) Adjustable High Limit (130° F to 160° F)



5351 East Thompson Road Suite 142 Indianapolis, IN 46237 P: 888.359.0362 F:317.489.5204

info@iOhvaccontrols.com www.iOhvaccontrols.com